

Day/Night Vandal Proof Camera NVC-BDN4402V



Features

- Mechanical IR cut filter
- IR operation capability
- Horizontal resolution: up to 650 TVL
- Min. Illumination: from 0.01 lx/F=1.2
- Digital Noise Reduction (DNR)
- Auto iris DC lens: f=2.8 ~ 10.5 mm
- 3-axis camera module adjustment
- Privacy zones: 4
- Other functions: mirror picture effect, motion detection
- Full configuration directly from the camera (user friendly OSD)
- IP 65
- Vandal proof housing
- Power supply: 12 VDC

| Specifications | Description |
|-------------------------------|---|
| Pick-up Element | 1/3" SONY Super HAD II CCD imager |
| Horizontal Resolution | 600 TVL - color mode, 650 TVL - B/W mode |
| Min. Illumination | 0.1 lx/F=1.2 - color mode (1/50 s), 0.01 lx/F=1.2 - B/W mode (1/50 s) |
| S/N Ratio | More than 50 dB (AGC Off) |
| Electronic Shutter | Auto (AES): 1/50 s ~ 1/120 000 s |
| Auto Gain Control (AGC) | On/Off |
| White Balance | 3 modes: Manual/ATW/AWB |
| Back Light Compensation (BLC) | On/Off |
| Synchronization | Internal |
| Day/Night Switching | Auto/Manual |
| Filter Delay | 1 ~ 15 s |
| Lens Type | Auto iris DC: f=2.8 ~ 10.5 mm |
| Angle of View (H) | 81° ~ 26° |
| Flickerless function | On/Off |
| Video Output | 1.0 Vp-p/75 Ohm (BNC) |
| Set-up | On Screen Display (OSD) |
| Privacy Zones | 4 |
| Other Functions | Digital Noise Reduction (DNR) Motion detection, Mirror picture effect, Image sharpness adjustment |
| Enclosure | Vandal proof, coated aluminium, impact resistant poly-carbonate bubble |
| Degree of Protection | IP 65 |
| Power Supply | 12 VDC |
| Power Consumption | 2.2 W |

| Specifications | Description |
|-----------------------|-------------------|
| Operating Temperature | -10°C ~ 45°C |
| Dimensions (mm) | 142 (Ø) x 100 (H) |
| Weight | 863 g |